





Speed, Performance, Value - The Right Balance

- Full range tare
- Overload protection
- Large 52mm backlit LCD display
- Rechargeable battery with up to 70 hours operation / mains adapter supplied as standard
- Large stainless steel platform
- Automatic memory accumulation
- Pre-set weighing with alarm
- Check-weighing with low and high limits
- Weighing
- Check weighing
- Weight accumulation



Technical Specifications

Model	CFM 60	CFM 150	CFM 300
Maximum capacity	60kg	150kg	300kg
Readability	5g	10g	20g
Tare range	-60kg	-150kg	-300kg
Repeatability (S.D.)	5g	10g	20g
Linearity (\pm)	10g	20g	40g
Platform size	425x525mm		

General Specifications

Typical stabilisation time	2 Sec
Units of measurement	Kilogram (kg), Pound (lb), Pound-Ounce (lb-oz)
Interface	RS-232 bi-directional Interface (Optional)
Operating temperature	0°C - 40°C
Power supply	9 VDC, 800 mA from external adapter, Internal Rechargeable Battery (up to 70 hours of operation)
Calibration	Automatic External
Display	1 x 6 digits 52mm backlit LCD
Housing	Indicator: ABS Plastic, Top Pan: Stainless Steel, Base: Cast Aluminium
Net weight	15kg

Key Accessories

- Adam Printer
- Thermal Paper Roll for Adam Printer
- RS-232 Bi-directional Interface



Supplied by

Wessex Scale Co,
 Lower Mill, Exford Nr Minehead Somerset TA24 7QE
 Tel: 0845 472 5345 Fax: 01643 800 299
 Email: sales@wessexscales.co.uk
 Website: www.wessexscales.co.uk

