

HL265/HL275

all stainless steel checkweighers - protection where you need it



stainless steel scales for the food industry

Wessex Scale Co

models HL265 & HL275 checkweighers

- protection where you need it

The **HL265** and **HL275** are a series of bench checkweighers particularly suited to the food industry. Capacities range from 1 kg up to 90 kg, with EU Trade Approval to 3000 divisions on the **HL265**, or non-approved to 6000 divisions on either model.

Protection where you need it -

- ◆ **In The Workplace** - The scale is fully stainless steel, including the load cell, and sealed to IP66 (NEMA 4X) for added protection in washdown environments.
- ◆ **In The Scale Base** - A 'Breakaway Load Transfer System' transfers shock loads and overloads away from the load cell, for added protection and reliability, giving up to 500% overload protection.
- ◆ **In the Pocket** - The rugged reliability comes to you at a very competitive price. A rapid-response display combines with the scale's superior accuracy to minimise your 'give-away'.



Specification

Capacity	*1 kg	3 kg	6 kg	15 kg	30 kg	45 kg	90 kg
Sensitivity							
Non-approved	0.2 g	0.5 g	1 g	2 g	5 g	10 g	20 g
†Approved	-	1 g	2 g	5 g	10 g	20 g	50 g
Pan size (mm) (W x D)	220 x 220		350 x 310		508 x 508		610 x 610

* Model HL275 only.

† Only model HL265 has approved specification.

- ◆ **Display type:** 7-segment LCD or LED.
- ◆ **Units:** kg, g, lbs, oz.
- ◆ **Displays:**
 - Model HL265:** 13 mm vacuum fluorescent or 17 mm LCD (essential if battery operation required). Three coloured LED's for Over/Under checkweighing.
 - Model HL275:** 13 mm vacuum fluorescent. Multi-coloured 45-segment graphics display for Over/Under checkweighing.
- ◆ **Power Supply:** 110 or 240 volts AC.
- ◆ **Battery Option:** 12 V DC for LCD version of Model **HL265** only. With 30 hours battery life, 14 hour re-charge time. Power-preserving shut down and low battery warning.
- ◆ **Column Option:** Both models are available with either a low head (135 mm to centre of display) or a column-mounted head (310 mm to centre of display). Remote head versions are also available.
- ◆ **Data Output Option:** An RS232 is available for all models.

Left: HL275 display illustrating Under, Accept & Over LCDs.

© Avery Weigh-Tronix group of companies 2008. All rights reserved. Avery Weigh-Tronix is a registered trade mark of the Avery Weigh-Tronix group of companies. This publication is issued to provide outline information only which, unless agreed by an Avery Weigh-Tronix group company in writing, may not be regarded as a representation relating to the products or services concerned. This publication was correct at the time of going to print however, Avery Weigh-Tronix reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service at any time.

Your local distributor:

Wessex Scale Co,
Lower Mill, Exford Nr Minehead
Somerset TA24 7QE
Tel: 0845 472 5345 Fax: 01643 800 299
Email: sales@wessexscales.co.uk
Website: www.wessexscales.co.uk